



[www.gsaudio.it](http://www.gsaudio.it)



## Competition Line Amplifier GS-120.4COMP

### General Specifications

Amplifier Tipology	Class D
Model	120.4COMP
Frequency Response	15 Hz - 20 KHz
Minimum Impedance	2 Ohm/CH
Bridge Output power @ 4 Ohm - 14.4V	2*220 WRMS
Normalized Output power @ 2 Ohm - 14.4V	4*120 WRMS
Normalized Output power @ 4 Ohm - 14.4V	4*60 WRMS

### Work Parameter

Power supply wire size (100% copper advice)	25 mmq
Obligatory Fuse on cable	80 A
Standby current	0.4 / 1.0 A
Maximum Peak current	60 A
Medium current musical use	15-30 A
Internal working voltage	(+/- 28V)
Efficiency @ 4 ohm	> 89%
Efficiency @ 2 ohm	> 85%
Efficiency @ 1 ohm	-
Minimum Voltage work (dangerous)	9.8 V
Maximum Voltage work (dangerous)	15.9 V

### Technical Parameter

Input sensitivity RCA	0.3 - 8 V
High level input	-
S/N ratio THD at 4 Ohm	> 95 db
Working led	Blue
Protection led	Red
Crossover FULL (CH3+4/CH2+1)	yes
Crossover HPF	40 Hz - 2 KHz
Crossover LPF	40 Hz - 2 KHz
Bass Boost Level	-
High Density Cast Aluminium Heatsink Body	
Thermally Efficient Heatsink Coating	
Low THD Audiophile Components	
T.D.O.S. Amplifier Protection Circuitry	
Damping Factor:	> 800
Remote bass controller	-

### Dimension / Package

Amplifier Height	60 mm
Amplifier Large	120 mm
Amplifier Length (include terminal)	110 mm
Amplifier Weight	0.8 KG
Package Weight	1.2 KG
Shipping box	165X150X90mm



**USER GUIDE**

<http://WWW.GSAUDIO.IT>

+39 347 3263458

@GSAUDIO\_ITALY