



www.gsaudio.it

Competition Serie Full-Range Amplifier GS-35000.1 SPL

General Specifications

Amplifier Tipology	Class D
Model	35000.1SPL
Frequency Response	20 Hz - 10 kHz
Minimum Impedance	1 Ohm
Output power @ 1 Ohm - 12.6V	31400 WRMS
Output power @ 2 Ohm - 12.6V	18700 WRMS
Output power @ 4 Ohm - 12.6V	12500 WRMS
Normalized Output power @ 1 Ohm - 14.4V	35000 WRMS
Normalized Output power @ 2 Ohm - 14.4V	21000 WRMS
Normalized Output power @ 4 Ohm - 14.4V	14000 WRMS

Working Parameters

Power supply wire size (100% copper advice)	8*100 mmq
Obligatory Fuse on cable	4*800 A
Standby current	6.8 / 9.0 A
Maximum Peak current	3200 A
Medium current musical use	800 - 1500 A
Internal working voltage	265 / 290 V
Efficiency @ 4 ohm	> 90%
Efficiency @ 2 ohm	> 86%
Efficiency @ 1 ohm	> 81%
Minimum Voltage work (dangerous)	9.3 V
Maximum Voltage work (dangerous)	15.9 V

Technical Parameters

Input sensitivity RCA	0.2 - 6 V
S/N ratio THD at 4 Ohm	> 86 dB
Working led	Blue
Protection led	Red
Clipping led	Orange
Crossover HPF	15 - 80 Hz / 12 dB
Crossover LPF	40 Hz - 10 kHz / 12 dB
Bass Boost Level	0 dB / +12 dB
Bass Boost frequency	45 Hz
High Density Cast Aluminium Heatsink Body	
Thermally Efficient Heatsink Coating	
Low THD Audiophile Components	
T.D.O.S. Amplifier Protection Circuitry	
Damping Factor	> 700
Remote bass controller	yes

Dimensions / Package

Amplifier Height	70 mm
Amplifier Large	225 mm
Amplifier Length (include terminal)	860 mm
Amplifier Weight	14 KG
Package Weight	14.5 KG
Shipping box	1040X260X100mm



USER GUIDE

<http://www.gsaudio.it>

+39 347 3263458

@GSAUDIO_ITALY